

## 7" TFT Customer Graphic Display

### Digital Picture Frame

Run a series of jpg images from the SD card provided. Promote specials and suggest add-ons.

### Pole Display

The GD7 includes a 2-line pole display function.



### Mini OCB

Like popular drive-thru order confirmation boards, the GD7 displays the entire order for confirmation. Promotes accuracy and reduces fraud.

### Includes SD Card

Digital images may be loaded onto the SD card provided with the GD7.

The innovative and revolutionary new GD7 Customer Graphic Display is suitable for visually promoting your product, promotions and specials. A slide show runs continuously on the screen next to the enhanced customer display. VESA mounting is also available for easy installation. Software is provided to control and configure the GD7 Graphic Display.

Think of the GD7 as a combination order confirmation screen, digital picture frame and a 2-line pole display. (Order confirmation and rotating images are not linked.) For about the same cost as a pole display, you can deliver much more. These displays really do turn heads.



# GD7 Customer Graphic Display



The GD7 Is Compatible With Many Popular SAM4s ECRs

## Features

- Supports JPEG Image Format
- 7 Inch TFT Panel
- Scrolling Images
- Able to Accept ESC/POS Commands for Text Display
- Supports Different Language Character Sets
- Built-in Real Time Clock
- Easy to Upgrade Firmware in the Field
- Also Supports VESA Mounting (75mm x 75mm)

## SAM4s Models Supported

- ER-285M (v1.027 or Later)
- ER-390M (v3.4 or Later)
- ER-650 Series (v10.8r)
- ER-5200M Series (v8.0 or Later)
- SER-7000 Series
- SPS-2000 (v3.00g27 or Later)
- SPS-500 Series Hybrid ECRs (v1.00m or Later)
- Check [www.crs-usa.com](http://www.crs-usa.com) for the Latest List

## Specifications

|                               |                                    |
|-------------------------------|------------------------------------|
| <b>LCD Size:</b>              | 7.0 Inches (Diagonal)              |
| <b>Resolution:</b>            | 480 x 234                          |
| <b>Active Area:</b>           | 6" W x 3.4" H                      |
| <b>Brightness:</b>            | 280 cd/m <sup>2</sup>              |
| <b>Driver Element:</b>        | a-Si TFT Active Matrix             |
| <b>Photo Format:</b>          | JPEG                               |
| <b>Serial Port:</b>           | One RS232                          |
| <b>Network Port:</b>          | Ethernet                           |
| <b>Memory Card:</b>           | SD Card (Included)                 |
| <b>Clock:</b>                 | Built-In Real Time Clock           |
| <b>Tilt Angle:</b>            | 0° ~ 35°                           |
| <b>Mounting:</b>              | VESA 75mm Compatible               |
| <b>Power Supply:</b>          | 12V DC 1.5A External Power Adapter |
| <b>Operating Temperature:</b> | 32° ~ 96°F (0° ~ 42°C)             |
| <b>Storage Temperature:</b>   | -12° ~ 158°F (-25° ~ 70°C)         |
| <b>Humidity:</b>              | 10% ~ 85% RH Non-Condensing        |
| <b>Dimensions:</b>            | 7-1/2"W x 9"H x 4" to 5" D         |



All product features are subject to change without notice.