







a Better Solution for your Business™

New standard for Impact Printer

SRP-275





The New standard For Impact Printers

The BIXOLON SRP-275 is an enhanced, more powerful successor to BIXOLO best-selling SRP-270 Series of receipt printers. The BIXOLON SRP-275 receipt printers. printer is compact, reliable and fast, and offers all of the easy-to-use feature important to retail, restaurant, and hospitality environments.

MAIN FEATURES WITH SPECIFICATIONS

Fastest printing in it's class

The SRP-275 is optimized for high-speed so customer receipts allowing kitchen orders print faster and quieter than ever. More than 5.1 lines per second and an integrated graphics memory produce receipts in shortest time without delaying customers or guests.

Drop in paper loading with paper width guide

For maximum efficiency, the SRP-275 offers drop-in paper loading to easily change the paper with one-hand.



Easy Paper Loading

Built-in power supply

The 220V AD adapter is elegantly integrated into the compact printer housing. Consequently, messing around with cables is avoided which is ideal at space-limited POS terminals or highly frequented cash desks.



Built-in Power Supply

Proven reliability

With an average performance of 18 million rows without failure, this printer gives you all reliability you need for long-term use and the autocutter for the SRP-275 is also guaranteed up to 1.5 million cuts with easy paper-jam removal.

User-friendly software tools



- PRINTING METHOD: 9 Pin Serial Dot Matrix
- PRINTING SPEED: 5.1 lines per second
- RESOLUTION : Horizontal Resolution : 80 dpi / Vertical Resolution : 144 dpi
- CHARACTER SIZE (W X H dots) : Font A : 9 X 9, Font B : 7 X 9 Korean : 17 X 9, Chinese : 16 X 16
- CHARACTERS PER LINE : FontA:35 (3half dot: 33) , Font B : 40 / Korean: 20, Chinese :22 (3half dot: 21)
- CHARACTER SET: Alphanumeric Character: 95

Chinese: 128 x 21

Extended Graphics Pages: Standard: 128 x 27

Korean: 128 x 1

International Character: 48

PAPER

WIDTH: 76 ± 0.5mm

• PAPER ROLL DIAMETER: Max Ø 83.0mm · PAPER LOADING: Drop in paper loading

RELIABILITY

• PRINTER UNIT: 18,000,000 Lines • TPH: 300 Million dots/wire

• AUTO CUTTER: 1,500,000 cuts

INTERFACE: Serial(RS-232C), Parallel (IEEE1284), USB, Ethernet

RECEIVE BUFFER: 8 Kbytes

NV IMAGE MEMORY: 256 Kbytes EMULATION: ESC/POS™

DRIVER: Windows Driver, OPOS Driver SENSOR: Paper Near End Sensor, Paper End Sensor,

Wall Mounting Paper Near End Sensor, Rear Cover Open Sensor

DRAWER PORT: 2 Drivers

POWER SUPPLY (SMPS): AC 100~240V / DC 24V, 1.5A **DIMENSIONS:** 160 X 239 X 157 (W X L X H mm) OPERATING TEMPERATURE: 0~40 °C / 32 ~ 104 °F

OPTIONS

- WALL MOUNT (RWM-350)
- SPLASH PROOF COVER (RSC-275) MELODY BOX (RMB-100)

BIXOLON® www.bixolon.com

This publication carries product description without obligation and is not to be seen as a firm offer. All specifications and design are subject to change without notice. February 2009