

# CAS DEP-50

## Receipt Printer



Printing System	Line thermal dot printing
Printing Width	48 mm (384 dots/line)
Dot Density	8 dots/mm (width, length)
Paper Feed Pitch	0.125 mm
Printing Speed	Approx. 11 lines/sec. (At Maximum)
Printing Columns & Character Size	32 columns (12 x 24 Font A) 1.25 x 3.00 mm 42 columns (9 x 16 Font B) 0.88 x 1.92 mm
Line Interval	Initial value: 4.23 mm (1/6 inch)
Character Types	Alphanumeric characters, symbols, international characters
Character Code	IBM Characters
Barcode Type	UPC-A/E, JAN (EAN) 13-/8-column, ITF, CODE 39, CODE 128, CODABAR
Paper	Thermal paper roll: 58 + 0/1mm x Ø83 (max) mm, 60 ~75 µm thick
Interface	Serial (RS-232C)
Input Buffer	64 KB
AC Adapter	Rated input: 100 ~ 240 V, 50/60 Hz, 40 VA Rated output: 12 V DC, 3A
Power Consumption	Non-Printing: Approx 2 W Printing: Approx 15 W (approx 20 W max)
Weight	Printer: 1.65 lbs / 750 grams AC Adapter: 0.77 lbs / 350 grams
Dimensions	4.17 (W) x 7.2 (D) x 4.96 (H) inches 106 (W) x 183 (D) x 126 (H) mm
Operating Temp	5 ~ 40 °C, 35 ~ 85 % RH (no dew condensation)
Storage Temp	-20 ~ 60 °C, 10 ~ 90% RH (no dew condensation)